

VALTORC

WWW.VALTORC.COM
AJBENTAL@VALTORC.COM
1 (866) VALTORC

BRASS SOLENOID VALVE

SERIES 810



BRASS SOLENOID VALVE SERIES 810

2-way, internally piloted, normally closed solenoid valve

1/4"-1/2"

Pipe Sizes

8W, 12W, 14W

Coils

2-300 psig

Operating Pressure



Materials of Construction

Body:	Brass
Armature Tube:	Stainless Steel 300
Fixed Core:	Stainless Steel 400
Plunger:	Stainless Steel 400
Spring:	Stainless Steel 300
Shading Ring:	Copper

Electrical Connection

Rating:	NEMA 4
Strain Relief Connector:	Model 09
1/2" Conduit Connector:	Model 01
6 ft. Power Cord:	Model 10



BUNA Sealing Material	14°- 280° F Temperature Range	Air, Inert gas, Water, Synthetic oils Medium Examples
---------------------------------	---	---

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
810-A	1/4"	7/16"	1.50	8	2	300/150
810-B	1/4"	7/16"	1.50	12	2	300/300
810-C	1/4"	7/16"	1.50	14	2	300/300
810-D	3/8"	7/16"	1.70	8	2	300/150
810-E	3/8"	7/16"	1.70	12	2	300/300
810-F	3/8"	7/16"	1.70	14	2	300/300
810-G	1/2"	7/16"	1.70	8	2	300/150
810-H	1/2"	7/16"	1.70	12	2	300/300
810-I	1/2"	7/16"	1.70	14	2	300/300

VITON Sealing Material	14°- 195° F Temperature Range	Air, Inert gas, Water Medium Examples
----------------------------------	---	---

Model #	Pipe Size (Inch)	Orifice Size (Inch)	Flow Factor (CV)	Watt Rating (W)	Min. Pressure (PSI)	Max. Pressure (AC/DC)
810-A	1/4"	7/16"	1.50	8	2	300/150
810-B	1/4"	7/16"	1.50	12	2	300/300
810-C	1/4"	7/16"	1.50	14	2	300/300
810-D	3/8"	7/16"	1.70	8	2	300/150
810-E	3/8"	7/16"	1.70	12	2	300/300
810-F	3/8"	7/16"	1.70	14	2	300/300
810-G	1/2"	7/16"	1.70	8	2	300/150
810-H	1/2"	7/16"	1.70	12	2	300/300
810-I	1/2"	7/16"	1.70	14	2	300/300